

hinen

Dongguan Hinen New Energy Technology Co., Ltd

Add: No.24 Dongkang Road, Dalingshan Town,
Dongguan City, Guangdong, China
Tel: +86 (769) 89920666 ext 8318
Email: service@hinen.com
Website: <https://www.hinen.com>

Europe HL Hinen B.V.

Add: John M. Keynesplein 1, 1066EP Amsterdam
Email: service@hinen.com
Tel: +86 (769) 89920666 ext 8318
Website: <https://nl.hinen.com>

Hinen South Africa (Pty) Ltd

Add: Ground floor, Block B, 100 West Street,
Sandton, Johannesburg 2196, South Africa
Email: SAfrica@hinen.com
Tel: +27 10 449 2306
Website: <https://za.hinen.com>

Hinen West Africa LIMITED

Add: 25A-2 Talabi St, Ogba, Lagos 101233, Lagos, Nigeria
Email: WAfrica@hinen.com
Tel: +86 (769) 89920666 ext 8318
Website: <https://ng.hinen.com>

Hinen Australia Pty. Ltd.

Add: Suite 503, Level 5, Tenancy 3, 107 Mount Street, North Sydney
Email: service@hinen.com.au
Tel: +61 2 7258 1272
Website: <https://au.hinen.com>

Hinen Energy Eastern Europe

Add: Wąska 95, 05-806 Sokółów Poland
Email: biuro@hinen.com
Tel: +48 606 807 712
Website: <https://pl.hinen.com>

Hinen Technology East Africa LIMITED

Add: No. 6, Kirichwa Lane Court, next to
GreenhouseMall, Ngong Road, Nairobi, Kenya
Email: EAfrica@hinen.com
Tel: +254789688999
Website: <https://ke.hinen.com>

10-25kW Three-phase Hybrid All-in-one RESS

A Series H10/15/20/25T +B8900M-HA

A10000T/A15000T/A20000T/A25000T

A10000T-E/A15000T-E/A20000T-E/A25000T-E

8.9 kWh-26.7 kWh/8.9 kWh-160.2 kWh



- ◆ 4 MPPT inputs, 120% Oversized PV input, Max 30 kW.
- ◆ Inverter parallel function, up to 6 units, Max. output power up to 150KW, massive energy storage of 160.2 kWh.
- ◆ Stackable integrated design, plug & play, no additional cable, saves 50% installation time.
- ◆ 120-600V ultra-wide battery voltage range, realizing 20KW charging & discharging capacity of one way battery.
- ◆ Support 100% three-phase unbalanced output.
- ◆ The phase sequence does not matter, ensuring easier and more flexible installation.
- ◆ Built-in change over switch, allows manual selection between Backup mode and By-pass mode for backup loads.
- ◆ Intelligent load management via dry contacts.
- ◆ Backup load transfer time \leq 10ms.

hinen

Technical Specification

Item	Model	A10000T A10000T-E	A15000T A15000T-E	A20000T A20000T-E	A25000T A25000T-E
PV Input Specification					
Recommended max. PV input power		30000W	30000W	30000W	30000W
Max. PV input voltage		1000d.c.V			
Startup voltage		120d.c.V			
Rated PV input voltage		600d.c.V			
PV voltage range		140d.c.V - 950d.c.V			
No. of independent MPPT inputs		4	4	4	4
No. of PV strings per MPPT		1/1/1/1	1/1/1/1	1/1/1/1	1/1/1/1
Max. input current per string		16/16/16/16 Ad.c.	16/16/16/16 Ad.c.	16/16/16/16 Ad.c.	16/16/16/16 Ad.c.
Max. short-circuit current		22/22/22/22 Ad.c.	22/22/22/22 Ad.c.	22/22/22/22 Ad.c.	22/22/22/22 Ad.c.
Max. inverter backfeed current to the array		0Ad.c.			
Battery Port Specification					
Battery type		Li-ion Battery			
Battery voltage		120d.c.V - 600d.c.V			
Max. charge / discharge current		45Ad.c./45Ad.c.			
Max. charge / discharge power		20000W/20000W	20000W/20000W	20000W/20000W	20000W/20000W
Max. short-circuit input current		210Ad.c.			
Communication		CAN			
Charging strategy		BMS instructions			
Battery expansion		1~3 series-connected 8.9kWh high-voltage battery modules per cluster			
Grid Port Specification					
Rated AC input apparent power		9999VA	15000VA	20000VA	20000VA
Max. AC input current		30.4Aa.c.	30.4Aa.c.	30.4Aa.c.	38Aa.c.
Rated AC output power		9999W	15000W	20000W	25000W
Rated AC output apparent power		9999VA	15000VA	20000VA	25000VA
Max. AC output current		15.2Aa.c.	22.8Aa.c.	30.4Aa.c.	38Aa.c.
Rated AC output current		14.5Aa.c.	21.8Aa.c.	29Aa.c.	36.3Aa.c.
AC output inrush current		68.8Aa.c.			
Max. backfeed short-circuit current		150Aa.c.			
AC input inrush current		56Aa.c.			
Rated AC voltage		400Va.c./230Va.c., 3L/N/PE			
Rated grid frequency		50Hz/60Hz			

Technical Specification

Item	Model	A10000T A10000T-E	A15000T A15000T-E	A20000T A20000T-E	A25000T A25000T-E
THDI @Full load		< 3%			
Power factor at rated power / Adjustable power factor		> 0.99 (0.8 leading – 0.8 lagging)			
Backup Port Specification					
Rated AC output apparent power		10000VA	15000VA	20000VA	20000VA
Rated AC output power		10000W	15000W	20000W	20000W
Max. AC output current		29Aa.c.	29Aa.c.	29Aa.c.	29Aa.c.
Peak AC output power		20000W	20000W	20000W	20000W
AC nominal voltage		400Va.c./230Va.c., 3L/N/PE			
AC nominal frequency		50Hz/60Hz			
THDV @Linear load		< 3%			
Back-up switch time		< 10ms			
Efficiency					
Max. efficiency		98.0%	98.0%	98.0%	98.0%
European efficiency		97.4%	97.4%	97.4%	97.4%
Protection & Function					
DC switch		yes			
PV reverse polarity protection		yes			
BAT reverse protection		yes			
Output AC overcurrent protection		yes			
Output AC overvoltage Protection		yes			
Anti-islanding protection		yes			
Residual current detection		yes			
Insulation resistance detection		yes			
Active anti-islanding method		yes (Frequency Shift)			
Over voltage category		DC type II/AC type III			
Protective class		Class I			
General Information					
Topology (solar / battery)		Transformerless/Transformerless			
Ingress protection rating		IP65			
Pollution degree classification		External (PD3), Internal (PD2)			
Dimensions (W * H * D)*		730 *637 *180 mm (±4mm)			
Weight*		59KG (±3KG)			

Technical Specification





Item	Model	A10000T A10000T-E	A15000T A15000T-E	A20000T A20000T-E	A25000T A25000T-E
Installation type		Floor stand			
Operating ambient temperature		-20 °C - 60 °C (> 45°C derating)			
Relative humidity (Non-condensing)		0% - 100%			
Cooling method		Fan cooling			
Noise(MAX)		< 45dB			
Max. operating altitude		3000m			
Wet locations classification		Yes			
Display		LCD+APP			
Monitor		RS485/WIFI			
DC connection		MC4			
AC connection		5P Connector			
Warranty*		10 years			
Country of manufacture		Made in China			
Certification & Standard					
Certification		CB, CE, UKCA, SONCAP, RCM, ROHS			
Standard		IEC/EN 62109-1, IEC/EN 62109-2, IEC 62619, IEC 60730-1 Appendix H, IEC/EN 62368-1, EN IEC 61000-6-1/3, IEC 61 000-2-2, CISPR 11, IEC 60529, IEC 60068-2-52, AS/NZS 4777.2, IEC 60947.1, AS 60947.3, VDE-AR-N 4105, EN 50549-1, G98, G99, UN 38.3, MSDS			

Dimensions (W * H * D)*: Total dimension of inverter and control box.

Weight*: Total weight of inverter and control box.

Warranty*: Refer to the product warranty terms for details.

Technical Specification

Model	A10000T/A15000T/A20000T/A25000T	
Hybrid inverter Rated AC output power Dimension (W*H*D) Weight	1000W / 15000W / 20000W / 25000W 730mm*637mm*180mm ≈59kg	
Control box	Built-In Grid / Backup / DC circuit Breaker	
Model	B8900M-HA	
High Voltage Battery Management System Operating Voltage Max.Charge / Discharge Current Operating Temperature Ingress Protection Dimension (W*H*D) Weight	135~583.2VDC 52A -20°C~60°C IP65 730*160*180mm ≈10kg	
Battery Module Battery Type Nominal Voltage Rated Capacity Rated Energy Max. Charge / Discharge Current Charge Temperature Discharge Temperature Ingress Protection Dimension (W*H*D) Weight	LiFePO ₄ (LFP) 172.8V 52Ah 8.985kWh 52A 0°C~55°C -20°C~60°C IP65 730*510*180mm 83kg	
Battery Module Base Dimension (W*H*D) Weight	730*40*180mm 5.8kg	